

Humco Holding Group, Inc.
7400 Alumax Drive
Texarkana, TX 75501
903-334-6200

Item #0395-0467

CAMPBOR SPIRITS USP

DATE PREPARED: 04/10/07

SECTION I

PRODUCT IDENTIFICATION

PRODUCT NAME: Camphor Spirits USP

SECTION II

HAZARDOUS COMPONENTS

Component	Percent	CAS No.
Ethyl Alcohol	84.0%	64-17-5
Camphor	10.0%	76-22-2

SECTION III

PHYSICAL DATA

Boiling Point: 170°F

Specific Gravity: (H₂O = 1) 0.824

Solubility: (In water) Insoluble

Vapor Pressure: (mmHg) NA

Vapor Density: (Air=1) NA

Evaporation Rate: NA

Appearance and Odor: Clear water white liquid with camphor odor.

% Volatiles by Volume: NA

SECTION III A

DEGREE OF HAZARD

Degree of Hazard

4 - Extreme	Flammability	3
3 - High	Health	3
2 - Moderate	Reactivity	0

1 - Slight
0 - Insignificant

Special Hazard 0

CAMPHOR SPIRITS USP

Page 2

SECTION IV FIRE AND EXPLOSION HAZARDS

Flash Point: 66°F

Extinguishing Media: Dry chemical, carbon dioxide, alcohol foam, water spray.

Special Firefighting Procedures and Precautions: When heated, material emits flammable and explosive vapors. If it can be safely done, remove containers from fire area.

Unusual Fire and Explosion Hazards: Firefighters should use self-contained breathing apparatus and full protective clothing.

SECTION V HEALTH HAZARD DATA

First Aid Instructions for Accidental Exposure:

If on Skin: Wash with soap and water. Get medical help if any irritation persists.

If in Eyes: Flush with running water for 15 minutes. Get medical attention immediately.

If Inhaled: Remove victim to fresh air. Get immediate medical assistance.

If Swallowed: Immediately give 3 to 4 glasses of water. **Do Not** induce vomiting. If vomiting occurs, give fluids again. Have physician determine if patient's condition allows induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unconscious or convulsing person.

SECTION VI REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to avoid: Strong oxidizing agents such as Potassium Permanganate & Chromic Anhydride.

Decomposition Products: Partial oxidation products and carbon monoxide from thermal-oxidation degradation.

SECTION VII SPILL AND DISPOSAL PROCEDURES

Steps to be taken in the event of a spill or discharge: Provide adequate ventilation. Remove sources of heat or ignition. Protect against inhalation of vapors and skin contact. Cover spill with dry sand or vermiculite and mix well prior to transferring to a disposal container. Keep container tightly closed.

Disposal Procedures: Scrap can be burned in a safe place or approved incinerator. Follow Federal, State and local regulations.

SECTION VIII INDUSTRIAL PROTECTIVE EQUIPMENT

Ventilation: To meet TLV requirements.

Respiratory Protection: Full face chemical cartridge respirator with an organic vapor cartridge to 200 mg/m₃

Eye Protection: Chemical safety goggles, eye wash station.

Skin Protection: Protective clothing for prolonged or repeated exposure.

SECTION IX SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Store in a cool, dry, well ventilated area away from oxidizing agents and sources of heat or ignition.