

Humco Holding Group, Inc.  
7400 Alumax Drive  
Texarkana, TX 75501  
800-662-3435

Item #0395-1250

**70% WINTERGREEN ALCOHOL**

**DATE ISSUED: 04/10/07**

-----  
**SECTION I HAZARDOUS PRODUCT/INGREDIENT PER 20 CFR 1910.1200**  
-----

<b>NO.</b>	<b>COMPOSITION</b>	<b>CAS NUMBER</b>	<b>PERCENT</b>
P	70% Wintergreen Alcohol	Mixture	100%
1	Isopropyl Alcohol	67-63-0	70%
2	Methyl Salicylate	119-36-8	0.4%

-----  
**SECTION II ACUTE TOXICITY DATA**  
-----

<b>NO.</b>	<b>ACUTE ORAL LD50</b>	<b>ACUTE DERMAL LD50</b>	<b>ACUTE INHAL. LC50</b>
1	5840 mg/kg (rats)	13000 mg/kg (rabbit)	12000 ppm (rat) 8 Hours
2	887 mg/kg (rats) 2.8 g/kg (rabbits)		

-----  
**SECTION III PHYSICAL DATA**  
-----

**Boiling Point:** (Deg F) 170°F  
**Melting Point:** (Deg F) -127°F for 70% Isopropyl Alcohol  
**Specific Gravity:** (H2O=1) 0.878  
**Solubility:** (In water) complete  
**Vapor Pressure:** (MM HQ) 29 at 20°C  
**Vapor Density:** (Air=1) 1.6 for Isopropyl Alcohol  
**Evaporation Rate (N-Butyl Acetate=1):** 1.7 for Isopropyl Alcohol  
**Appearance and Odor:** Clear, green liquid with Methyl Salicylate and alcohol odor.

-----  
**SECTION III A DEGREE OF HAZARD**  
-----

Degree of Hazard		
4 - Extreme	Flammability	3
3 - High	Health	1
2 - Moderate	Reactivity	0
1 - Slight	Special Hazard	0
0 - Insignificant		

---

**SECTION IV FIRE AND EXPLOSION HAZARDS**

---

**Flash Point and Method:** 68°F Tag Open Cup

**Extinguishing Media:** Alcohol foam, CO<sub>2</sub>, dry chemical, water spray.

**Special Firefighting Procedures and Precautions:** **Warning** - Flammable. Clear fire area of unprotected personnel. **Do not** enter confined space without full bunker gear (helmet with full face shield, bunker coat, gloves, and rubber boots) including a positive pressure, NIOSH approved self contained breathing apparatus. Cool fire exposed containers with water.

**Unusual Fire and Explosion Hazards:** Containers exposed to intense heat should be cooled with water to prevent vapor pressure build up which could result in a rupture. Container area exposed to direct flame contact should be cooled with large amounts of water, as needed to prevent weakening of container structure.

**Flammable Limits/% Volume in Air:**

**Lower:** 2.0                      **Upper:** 12.0 for 70% Isopropyl Alcohol

---

**SECTION V HEALTH HAZARD INFORMATION**

---

OSHA PEL/TWA      400ppm  
OSHA PEL/CEILING 400ppm  
ACGIN TLV/TWA    800ppm

**Inhalation:** May cause mild irritation to the nose, throat, and respiratory tract and may result in central nervous system (CNS) depression.

**Skin Contact:** May cause mild skin irritation.

**Skin Absorption:** May cause mild skin irritation.

**Eye Contact:** Moderately irritating to the eyes.

**Ingestion:** Generally considered to have a low order of acute oral toxicity.

**Acute:** Acute local irritation is slight, while the acute systemic ingestion and inhalation exposure is considered to be moderate.

**Chronic:** Chronic systemic ingestion exposure is considered to be slight while the inhalation exposure is considered to be moderate.



---

**SECTION IX ENVIRONMENTAL PROTECTION**

---

**Spill or Leak Procedures: Warning - Flammable.** Eliminate all ignition sources. Equipment must be grounded to prevent sparking. **Large spills -** evacuate the area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak, if safe to do so. Dike and contain. **Small spills -** take up with absorbent material and place in non-leaking containers. Seal tightly for disposal.

**Waste Disposal:** Under E.P.A.-R.A.C.A. (40CFR261.21), if this product becomes a waste material, it would be ignitable hazardous waste, hazardous waste number D001. Refer to latest E.P.A. or state regulations regarding proper disposal.

**Environmental Hazards:** Under E.P.A. comprehensive environmental response, compensation and liability act, under E.P.A.-CERCLA (Superfund) releases to air, land, or water may be reportable to the National Response Center, 1-800-424-8802, (circumstances surrounding the release and cleanup determine reportability).

---

**SECTION X SPECIAL PROTECTION INFORMATION**

---

**Ventilation Requirements:** Use explosion-proof ventilation as required to control vapor concentrations.

**Other Clothing and Equipment:** Eye wash fountains and safety showers should be available for emergency use.

**Eye:** Refer to Section VIII.

**Respiratory:** Refer to Section VIII.

---

**SECTION XI TRANSPORTATION DATA**

---

**HAZARDOUS CHARACTERISTICS:** Flammable Liquid

**D.O.T. Classifications:** Flammable Liquid N.O.S. Contains Isopropanol UN 1993